



Alpha Chemika



ISO 9001 QUALITY SYSTEM CERTIFIED ORGANIZATION

MATERIAL SAFETY DATA SHEET

MSDS

Savgan Heights : 102 ,B Wing ; R.T.O. Lane ,Andheri (West) Mumbai - 400053 , INDIA

Section 1 - Chemical Product and Company Identification

Product Name : ALUMINUM NITRATE

Synonyms: Aluminum (III) nitrate, nonohydrate (1:3:9); Nitric acid, aluminum salt; Aluminum nitrate,

CAS No.: 7784-27-2 (Nonahydrate)

Molecular Weight: 375.

Chemical Formula: $\text{Al}(\text{NO}_3)_3 \cdot 9\text{H}_2\text{O}$

Section 2 - Composition, Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Aluminum Nitrate	7784-27-2	98 - 100%	Yes

Section 3 - Hazardous Identification

Emergency Overview

DANGER! STRONG OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT.

SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 2 - Moderate

Flammability Rating: 0 - None

Reactivity Rating: 3 - Severe (Oxidizer)

Contact Rating: 2 - Moderate

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES

Storage Color Code: Yellow (Reactive)

Potential Health Effects

Inhalation:

Causes irritation to the respiratory tract. Symptoms may include coughing, shortness of breath.

Ingestion:

May cause gastroenteritis and abdominal pains. Purging and diuresis can be expected. Rare cases of nitrates being converted to the more toxic nitrites have been reported, mostly with infants.

Skin Contact:

Causes irritation to skin. Symptoms include redness, itching, and pain.

Eye Contact:

Causes irritation, redness, and pain.

Chronic Exposure:

Small repeated oral doses of nitrates may cause weakness, depression, headache, and mental impairment.

Aggravation of Pre-existing Conditions:

Persons with stomach diseases and infants are much more sensitive to nitrate ion toxicity.

Section 4 - First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion:

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

Skin Contact:

Wipe off excess material from skin then immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get medical attention.

Section 5 - Fire Fighting Measures

Fire:

Not combustible, but substance is a strong oxidizer and its heat of reaction with reducing agents or combustibles may cause ignition. When heated, gives off oxygen thus increasing fire hazard.

Explosion:

Contact with oxidizable substances may cause extremely violent combustion. Some nitrates may explode when shocked, exposed to heat or flame, or by spontaneous chemical reaction.

Fire Extinguishing Media:

Use water or water spray only. Water spray may be used to keep fire exposed containers cool.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. This oxidizing material can increase the flammability of adjacent combustible materials.

Section 6 - Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8.

Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover spill with sodium bicarbonate or soda ash and mix.

Section 7 - Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Separate from incompatibilities. Separate from combustible, organic, or any other readily oxidizable materials. Do not store on wooden floors. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

Section 8 - Exposure Controls, Personal Protection

Airborne Exposure Limits:

-OSHA Permissible Exposure Limit (PEL):

15 mg/m³ (TWA) total dust and 5 mg/m³ (TWA) respirable fraction for Aluminum metal as Al.

-ACGIH Threshold Limit Value (TLV):

1 mg/m³ respirable fraction (TWA), Aluminum metal and Insoluble compounds, A4.

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest..

A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Rubber or neoprene gloves and additional protection including impervious boots, apron, or coveralls, as needed in areas of unusual exposure.

Eye Protection:

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

Section 9 - Physical and Chemical Properties

Appearance:

White crystals.

Odor:

Odorless.

Solubility:

Very soluble.

Specific Gravity:

No information found.

pH:

Aqueous solution is acidic.

% Volatiles by volume @ 21C (70F):

0

Boiling Point:

135C (275F) Decomposes.

Melting Point:

73C (163F)

Vapor Density (Air=1):

No information found.

Vapor Pressure (mm Hg):

No information found.

Evaporation Rate (BuAc=1):

No information found.

Section 10 - Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Oxides of nitrogen.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Reducing agents, organic materials, cyanides, thiocyanides, acids, and heavy metals.

Conditions to Avoid:

Heat, shock, friction, incompatibles.

Section 11 - Toxicological Information

(9-hydrate): Oral rat LD50: 3671 mg/kg; Investigated as a reproductive effector.

-----\Cancer Lists\-----

---NTP Carcinogen---

Ingredient	Known	Anticipated	IARC Category
Aluminum Nitrate (7784-27-2)	No	No	None

Section 12 - Ecological Information

Environmental Fate:

No information found.

Environmental Toxicity:

No information found.

Section 13 - Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

Section 14 - Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: ALUMINUM NITRATE
Hazard Class: 5.1
UN/NA: UN1438
Packing Group: III
Information reported for product/size: 300LB

International (Water, I.M.O.)

Proper Shipping Name: ALUMINUM NITRATE
Hazard Class: 5.1
UN/NA: UN1438
Packing Group: III
Information reported for product/size: 300LB

Section 15 - Regulatory Information

-----\Chemical Inventory Status - Part 1\-----
Ingredient TSCA EC Japan Australia

Aluminum Nitrate (7784-27-2) Yes Yes Yes Yes

-----\Chemical Inventory Status - Part 2\-----
--Canada--
Ingredient Korea DSL NDSL Phil.

Aluminum Nitrate (7784-27-2) Yes Yes No Yes

-----\Federal, State & International Regulations - Part 1\-----
-SARA 302- -SARA 313-----
Ingredient RQ TPQ List Chemical Catg.

Aluminum Nitrate (7784-27-2) No No No Nitrate Cmpd

-----\Federal, State & International Regulations - Part 2\-----
-RCRA- -TSCA-
Ingredient CERCLA 261.33 8(d)

Aluminum Nitrate (7784-27-2) No No No

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No
SARA 311/312: Acute: Yes Chronic: Yes Fire: Yes Pressure: No
Reactivity: No (Pure / Solid)

Section 16 - Additional Information

Not Regulated